Deck Stand

Our deck stand is available in robust steel construction with an epoxy primer containing rust-inhibiting pigments and an epoxy enamel topcoat. Also available with SS316 stainless-steel housing.

Valve position is indicated by a pointer attached to a bronze nut that travels along the internal stainless-steel stem. A machined slot in the housing guides the pointer's movement, while two end stops protect it from damage caused by overtravel.

Engineered for harsh environments, the fully enclosed housing combines a lip seal and a transparent acrylic cover across the pointer slot. This design protects the internal stem thread from water and debris while providing unhindered visual monitoring of valve position.

Shaft Options

Diameters:
20 mm, 25 mm and 32 mm

Materials:
Stainless steel 304L or 316L

Connections:
Round with Pin Hole,
Keyway, Square, Hexagonal



Height above deck: 350 mm
Handwheel diameter: 150 mm



Height above deck: 800 mm
Handwheel diameter: 350 mm



Adjustable gland packing
for watertight sealing

Deck Stand Options

- Orientation: vertical, horizontal or inverted.
- Watertight sealing: gland packing, lip seal or O-ring.
- Limit switches for remote valve position feedback.
- Handwheel diameter: 150 mm to 800 mm.
- Height above deck: 350 mm to 1200 mm.
- Handwheel padlock lockout assembly.



Limit switches for
remote valve position feedback

TASARO SINGAPORE PTE LTD
1 Sunview Road #02-02 Eco-Tech@Sunview Singapore 627615 | Tel: +65 6445 3692 | Email: info@tasaro.com | URL: www.tasaro.com